

# Declaration of Performance

EC Construction Products Regulation EN

12326 Roofing & Cladding Slate



**PRIMERA**  
FINEST NATURAL SLATE

86 Ramsey Road  
Warboys  
Huntingdon  
Cambridgeshire  
PE28 2RW  
Tel: +44 (0)1487 825 222  
Fax: +44 (0)1487 825 240  
info@primeraslate.co.uk  
[www.primeraslate.co.uk](http://www.primeraslate.co.uk)

DOP Number:		DOP 19/002			
1. Unique identification code of the product-type:		La Luz Zamora Estella			
2. Type, batch or serial number or any other element allowing identification of the construction product:		30X20 35x20 40x20 40x25 50x25 50X30 60X30			
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:		Slate for discontinuous roofing and cladding			
4. Name, registered trade name or registered trade mark and contact address of the manufacturer:		Pizarras La Luz S.L. La Ermita, 1. Riofrio de Aliste, Spain			
5. Where applicable, name and contact address of the authorised representative:		N/A			
6. System or systems of assessment and verification of consistency of performance of the construction product:		System 4			
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:		The manufacturer has carried out factory production control and determination of product type based upon System 4 within the Assessment of Conformity Tasks.			
8. In case of the declaration of performance concerning a construction product covered by a European Technical Assessment:		N/A			
<b>9. Declared Performance:</b>					
Essential Characteristic for Pitched Roof Coverings:	Performance:		Harmonized Technical Specification:		
Mechanical Resistance:	Mean Failure Load:		EN12326-2:2011		
	Transverse: 816,7N	Longitudinal: 976,4 N			
	Characteristic MOR:				
	Transverse: 62,4Mpa	Longitudinal: 73,2 Mpa			
External Fire Performance:	Deemed to satisfy		EC Decision 2000/553/EC		
Reaction to Fire:	Deemed to satisfy Class A1		EC Decision 96/603/EC as amended		
Dimensional Variation:			EN12326-2:2011		
Slate Type:	Very Smooth	Smooth		Normal	Textured
Deviation from flatness:	<1.0%				
Nominal thickness and variation:	5mm +/- 35%				
Deviation from declared width:	+/- 5mm				
Deviation from declared length:	+/- 5mm				
Deviation from straightness of edges:	+/- 5 mm				
Deviation from rectangularity:	+/- 1%				
Durability:				EN12326-2:2011	
Water absorption:	Code A1 0.25%				
Freeze thaw:	Not Required				
Thermal cycle test:	Code T1				
Carbonate content:	0.9%				
Sulphur dioxide exposure tests:	Code S1				
Non-carbonate carbon content:	0.4%				
Release of dangerous substances:	None in conditions of use as roofing or external cladding		EN12326-2:2011		
10. Declaration: The product(s) identified in Points 1 and 2 is in conformity with the declared performance under point 9. This declaration of performance is the sole responsibility of the manufacturer identified in point 4.					
Place & Date of Issue: PRIMERA SLATE COMPANY LIMITED 86 Ramsey Road, Warboys, Huntingdon, Cams PE28 2RW 1 <sup>st</sup> April 2019		Name: Mr Stephen Harding Position: Managing Director Signature: 			